Reply to Final Office Action of August 17, 2010

DO NOT ENTER: /K.G./

11/22/2010

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

<u>Listing of Claims:</u>

1-16. (Canceled)

17. (Previously presented) A corrosion resistant member comprising a Y₂O₃ sintered material that includes 99.9% by weight or more Y in terms of Y₂O₃, wherein

said Y_2O_3 sintered material comprises at least metal element of AE, wherein AE is a group II element of the periodic table, and

wherein a difference in crystal grain size between the surface and the inside region of said Y_2O_3 sintered material is not larger than 30 μm .

- 18. (Previously presented) The corrosion resistant member according to claim 17, wherein said Y₂O₃ sintered material further comprises any one of Si, Fe and Al.
- 19. (Currently amended) The corrosion resistant member according to claim 17, wherein said Y₂O₃ sintered material further comprises any of a group of metallic elements consisting of Si, Fe, Al and AE (these metallic elements will hereinafter be collectively referred to as metal elements M), in concentrations of 300 ppm of less for Si in terms of SiO₂, 50 ppm or less for Fe in terms of Fe₂O₃, 100 ppm or less Al in terms of Al₂O₃ and 350 ppm or less AE, wherein AE is a group II element of the periodic table, in terms of AEO, wherein AEO is a compound containing the AE and O.

[

Attorney Docket No. 374611-000162 Customer No. 73230

Appl. No. 10/566,332 Amdt. Dated Reply to Final Office Action of August 17, 2010

- 20. (Previously presented) The corrosion resistant member according to claim 19, wherein the content ratio of any of the metal elements M contained at and near the surface to that contained deep inside of said Y₂O₃ sintered material is in a range from 0.2 to 5.
- 21. (Previously presented) The corrosion resistant member according to claim 17, wherein said Y_2O_3 sintered material shows dielectric loss tangent of 2 x 10^{-8} or less in a frequency range from 10 MHz to 5 GHz.
- 22. (Currently amended) The corrosion resistant member according to claim 17, wherein the having a carbon content in said Y₂O₃ sintered material that is 100 ppm by weight or less.
- 23. (Previously presented) The corrosion resistant member according to claim 17, wherein said Y₂O₃ sintered material has void ratio of 5% or less.
- 24. (Previously presented) The corrosion resistant member according to claim 17, wherein said Y₂O₃ sintered material has density of 4.8 g/cm³ or higher.

25-27. (Canceled)